

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、注册、企业名称、商号、域名、其他知识产权外，所有权利均保留。未经许可，不得复制或传播。

FOR-1755 Rev.1.6

2





3

4

5

6

未注公差/General tolerances (mm)														 0.1/10
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	
3	6	10	18	30	50	80	120	180	250	315	400	500	>500	±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



Only 02-06 Poles
there are the stick
points on both sides

Note:

The A&Z(H) in the name means: A(H) and Z(H).

5	Clamp	Copper Alloy	Sn Plated
4	Screw	Steel	M2/Zn Plated
3	Cage	Copper Alloy	M2/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/8	/	300/8
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	/	/	250/7
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	/	2.5
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M2, 0.2/1.77		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	28~16/ 0.5~1.5		
间距/Pitch(mm)/线数范围/Poles	3.5/N=02~24P		
剥线长度/Stripping length(mm)	6~7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE / RAL	/		

		MATERIAL:	SURFACE/COLOR:	
MAT NO./REV: - / 00		MAT STATUS: 批量		
APPD: 兰春华	2022.08.17	NAME 15EDGK-3.5-XXP-1Y-00A&Z(H)		
CHKD: 龚耀志	2022.08.16			
DRFT: 胡松	2022.08.16	DRAWING NO.	TYPE	DRAWING STATUS
200083554	CUSTOMER DRAWING	已发布	SCALE	SHEET
2:1	1/1			

00			胡松	2022.08.16
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6