






Technical characteristics:

Specifications

DIN EN 60 664-1
DIN EN 61 984

Inserts

- 01. Number of contacts :16+PE
- 02. Rated Current :16A
- 03. Rated Voltage :500V
- 04. Pollution degree :3
- 05. Rated impulse voltage :6kv
- 06. Insulation resistance :≥10¹⁰ Ω
- 07. Material:Polycarbonate
- 08. Rated voltage acc. to UL/CSA:600V
- 09. Limiting temperatures : -40℃~+125℃
- 10. Flammability acc.to UL94:V0
- 11. Mechanical working life (mating cycles) :≥500

contacts

- 01. Material:Copper alloy
- 02. Surface:hard-silver plated
- 03. Terminal :Push-in terminal
- 04. Wire gauge :0.5-2.5mm² (AWG 20-14)
- 05. Stripping length :8-10mm

Note:Use only flexible wires with cold heads

MATERIAL:				SURFACE:					
MAT NO.:				 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD					
STATUS:									
APPD: Zhou X 2021.07.13				NAME:					
CHKD: Yang SH 2021.07.13				DE-016-MP					
DRAFT: Chen HK 2021.07.13				DRAWING NO.: /					
REV		ECN		DESCRIPTION		DRAFT		DATE	