





未注公差/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	~2.50	±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



5	Button	POM	UL94HB
4	Spring	Stainless steel	/
3	Pin header	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage(V)/Current(A)		300/15	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		Ⅲ/3	Ⅲ/2
额定电压/电流/Rated Voltage(V)/Current(A)		/	450/17
工频耐压/Withstanding Voltage(V/1Min)			AC2500
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)			0.2~2.5/28~12
间距/Pitch(mm)/线数范围/Poles			5.0/N=01~24P
剥线长度/Stripping length(mm)			5~6
使用温度范围/Operating temperature(°C)			-40~+105
符合RoHS环保要求/Conform to RoHS			Yes

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/	NAME: DG243-5.0-XXP-1Y-00A(H)	
APPD: Li GL 2020.06.10		DRAWING NO.: DG243-5.0-C01	
CHKD: MaEK 2020.06.10		REV	TO
DRFT: WangW 2020.06.10		TYPE: CUSTOMER DRAWING	
SIZE: A4	mm (inch)	SCALE: 2:1	SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE