

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利外，其他所有权利均归本公司所有。未经许可，不得复制或传播。本公司保留对设计、发明、实用新型和外观设计的所有权利。

FOR-1755 Rev.1.7

2







3

4

5

6

PCB LAYOUT



Note: The A&Z(H) in the name means: A(H) and Z(H).

5	Cover	PA66	UL94V-0
4	Housing	PA66	UL94V-0
3	Button	PA66	UL94V-0
2	Small Pin header	Copper alloy	Sn Plated
1	Big Pin header	Copper alloy	Sn Plated
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)		300/2	300/2	300/2
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)		/	250/2	/
工频耐压/Withstanding voltage(V/1Min)		AC2000		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)		24~20 / 0.2~0.5		
间距/Pitch(mm)/线数范围/Poles		2.5/N=01~30P		
剥线长度/Stripping length(mm)		8.5~9.5		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

			MATERIAL: -			SURFACE/COLOR:						
			MAT NO./REV: - / 00			MAT STATUS: 批量						
APPD: 兰春华	2022.08.18		NAME									
CHKD: 陈招	2022.08.18		DG250-2.5-XXP-1Y-00A&Z(H)									
DRFT: 袁路易	2022.08.18		DRAWING NO.		TYPE		DRAWING STATUS		SCALE		SHEET	
 A4			200022093		CUSTOMER DRAWING		已发布		3:1		1/1	

00	ECN	DESCRIPTION	DRFT	DATE
袁路易	2022.08.18			

1

2

3

4

5

6