

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless and until authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、域名权、其他知识产权等权利外，本公司保留所有权利。未经授权，不得复制或传播本文件内容。违反者将承担法律责任。所有权利保留。

FOR-1755 Rev.1.7

2






3

4

5

6

未注公差/General tolerances(mm)														 0.1/10  ±2°
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



Note:The A&Z(H) in the name means:A(H) and Z(H).

4	Screw	Steel	M3/Zn plated
3	Clamp	Copper alloy	Sn plated
2	Cage	Copper alloy	M3/Ni plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/10	/	/
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		/	250/12	/
工频耐压(V/1Min)/Withstanding voltage(V/1 Min)		AC2000		
螺丝扭矩/Torque Tightening(N·m/Lb.in)		M3, 0.5/4.43		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG)		28~14/2.5		
间距/Pitch(mm)/线数范围/Poles		5.0/N=02~20P		
剥线长度/Stripping length(mm)		5~6		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

		MATERIAL:		SURFACE/COLOR:	
APPD: David		2022.12.09		MAT NO./REV:	
CHKD: David		2022.12.09		MAT STATUS: 批量	
DRFT: 曹心一		2022.12.09		NAME	
DRAFTING: 曹心一		2022.12.09		DG331-5.0-XXP-1Y-00A&Z(H)	
DRAWING NO.		TYPE		DRAWING STATUS	
200022230		CUSTOMER DRAWING		work	
SCALE		SHEET		1/1	
2:1					

00			曹心一	2022.12.09
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6