

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利权外，本公司保留所有权利。未经许可，不得复制或传播。违反者将承担赔偿责任。所有权利保留。

FOR-1755 Rev.2.0



2

3

4


5

6



未注公差/General tolerances (mm)

0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.1/10 ±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



7	Slider	Stainless steel	/
6	Spring 2	Stainless steel	/
5	Spring 1	Stainless steel	/
4	Current carrier	Copper	Sn Plated
3	Lever	PA66+GF	UL94V-0
2	button	PA66+GF	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/40	600/40	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/41	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	20~8/0.5~6&10(sol)		
间距/Pitch(mm)/线数范围/Poles	8.2/01P		
剥线长度/Stripping length(mm)	10~12		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

		MATERIAL:		SURFACE/COLOR:	
APPD: 李根芳		MAT NO./REV:		MAT STATUS: work	
CHKD: 马恩升		NAME		DSW6-TW-01P-1Y-00Z (H)	
DRFT: 王林祥		DRAWING NO.		DRAWING STATUS	
2023.09.27		200254283		work	
A4		TYPE		SCALE	
CUSTOMER DRAWING		1:1		SHEET	
1/1					

00		/	王林祥	2023.09.27
REV	ECN	DESCRIPTION	DRFT	DATE