


VINYL-INSULATED (EASY ENTRY) RING TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16
AMP.	9	12	17	18

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
INSULATION MATERIAL: VINYL
INSULATION COLOR:

22-16 A.W.G.: RED

TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION ^{inch} _{mm}							CRIMPING TOOL	Q'TY BOX					
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T							
22-16 A.W.G.	RVEB1-2	RVE1-2	#2	.087 2.2	.217 5.5	.197 5.0	.720 18.3	.441 11.2	.157 4.0	.067 1.7	.030 0.75	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:RED	1000					
	RVEB1-2.5	RVE1-2.5	#2	.095 2.4			.732 18.6						1000					
	RVEB1-3.2	RVE1-3.2	#4	.126 3.2			.736 18.7						1000					
	RVEBS1-3.7	RVES1-3.7	#6	.146 3.7									1000					
	RVEBM1-3.7	RVEM1-3.7	#6	.146 3.7	.260 6.6	.248 6.3	.811 20.6						1000					
	RVEBL1-3.7	RVEL1-3.7	#6	.146 3.7	.315 8.0	.276 7.0	.866 22.0						1000					
	RVEBS1-4	RVES1-4	#8	.169 4.3	.260 6.6	.248 6.3	.811 20.6						1000					
	RVEBL1-4	RVEL1-4	#8	.169 4.3	.315 8.0	.276 7.0	.866 22.0						1000					
	RVEB1-5	RVE1-5	#10	.209 5.3	.457 11.6	.433 11.0	1.102 28.0						1000					
	RVEBL1-5	RVEL1-5	#10	.209 5.3									1000					
RVEB1-6	RVE1-6	1/4	.252 6.4	1000														
RVEB1-7	RVE1-7	1/4	.291 7.4	1000														
0.5-1.5 mm ²	RVEB1-8	RVE1-8	5/16	.331 8.4	.535 13.6	.547 13.9	1.248 31.7						1000					
	RVEB1-10	RVE1-10	3/8	.413 10.5									1000					
	RVEBL1-10	RVEL1-10	3/8	.413 10.5									1000					
	RVEB1-12	RVE1-12	1/2	.512 13.0	.772 19.6	.630 16.0	1.441 36.6						1000					
	RVEB1-13	RVE1-13	9/16	.591 15.0	.543 13.8		1000											
	RVEB1-14	RVE1-14	9/16	.591 15.0	1.063 27.0	.827 21.0	1.791 45.5						1000					
	RVEB1-16	RVE1-16	5/8	.669 17.0									1000					
RVEB1-20	RVE1-20	3/4	.827 21.0	1000														

UL cUL ALL LISTED