

VINYL-INSULATED (EASY ENTRY) SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	12	10
AMP.	35	50


MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: VINYL

INSULATION COLOR:

12-10 A.W.G.: YELLOW

TERMINAL MATERIAL: COPPER



WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION inch mm							CRIMPING TOOL	Q'TY BOX
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T		
12-10 A.W.G.	SVEBS5-3.7	SVES5-3.7	#6	.146 3.7	.283 7.2	.295 7.5	1.004 25.5					IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:YELLOW	500
	SVEB5-3.7	SVE5-3.7	#6	.146 3.7	.327 8.3	.276 7.0	1.047 26.6						500
	SVEBSS5-4	SVES5-4	#8	.169 4.3	.283 7.2	.295 7.5	1.004 25.5						500
	SVEBS5-4	SVES5-4	#8	.169 4.3	.327 8.3								500
	SVEBL5-4	SVEL5-4	#8	.169 4.3	.354 9.0								500
4-6 mm ²	SVEBS5-5	SVES5-5	#10	.209 5.3	.319 8.1	.276 7.0	1.047 26.6	.555 14.1	.248 6.3	.134 3.4	.039 1.0		500
	SVEB5-5	SVE5-5	#10	.209 5.3	.354 9.0								500
	SVEBS5-6	SVES5-6	1/4	.252 6.4									500
	SVEBL5-6	SVEL5-6	1/4	.252 6.4	.472 12.0	.472 12.0	1.283 32.6						500
	SVEB5-8	SVE5-8	5/16	.331 8.4	.551 14.0	.413 10.5	1.244 31.6						500

UL cUL ALL LISTED