

TERMINAL BLOCKS FOR P.C.B. RISING CLAMP

MORSETTI PER C.S. CARRELLO

BLOCS DE JONCTION C.I. ÉTRIER REMONTANT


PRINTKLEMMEN LIFTPRINZIP

CPP

Interlocking modules · Modulo componibile
Elements modulaires · Zusammensteckbare Blöcke



Poles · Poli · Pôles · Polzahl

2/3



3,5 - 3,81		
Pitch Pas	Passo Rastermaß	mm
Rated Voltage Tensione nominale Tension nominale	160	V
Rated Current Corrente nominale Bemessungsstrom	10	A
Types of cables Type du conducteur Nominal cross section Sezione nominale Sektion nominale	0,2 ÷ 1,5 30 ÷ 16	mm² AWG
Stripping length Lunghezza spelatura Longueur de dénudage	6	mm
Torque Couple de serrage Coppia di torsione Drehmoment	0,3 / 1,5	Nm Lb-in
Temperature Température Temperatur	110	°C
Housing Corps isolant Corpo isolante Isolierkörper	PA - UL 94 V0	
Captive Screw Vis Imperdable Vite Imperdibile Unverlierbare Schraube	M2	
	0,5 x 2,5	
V	A	mm²/AWG
130	10	0,2 ÷ 1
130	10	0,2 ÷ 1
300	10	30 ÷ 16

min 2 - max...		
VE	/ on demand GR GR1 NE AR BL RO GI	
D/A1		



CPP

Interlocking modules · Modulo componibile
Elements modulaires · Zusammensteckbare Blöcke



Poles · Poli · Pôles · Polzahl

1/2



7 - 7,62		
Pitch Pas	Passo Rastermaß	mm
Rated Voltage Tensione nominale Tension nominale	400 - 500	V
Rated Current Corrente nominale Bemessungsstrom	10	A
Types of cables Type du conducteur Nominal cross section Sezione nominale Sektion nominale	0,2 ÷ 1,5 30 ÷ 16	mm² AWG
Stripping length Lunghezza spelatura Longueur de dénudage	6	mm
Torque Couple de serrage Coppia di torsione Drehmoment	0,3 / 1,5	Nm Lb-in
Temperature Température Temperatur	110	°C
Housing Corps isolant Corpo isolante Isolierkörper	PA - UL 94 V0	
Captive Screw Vis Imperdable Vite Imperdibile Unverlierbare Schraube	M2	
	0,5 x 2,5	
V	A	mm²/AWG
450	10	0,2 ÷ 1
450	10	0,2 ÷ 1
300	10	30 ÷ 18

min 2 - max...		
VE	/ on demand GR GR1 NE AR BL RO GI	
D/A1		




CPA

Single block · Blocco unico
Monobloc · Einzelblock



Poles · Poli · Pôles · Polzahl

2/20



3,5 - 3,81		
Pitch Pas	Passo Rastermaß	mm
Rated Voltage Tensione nominale Tension nominale	160	V
Rated Current Corrente nominale Bemessungsstrom	10	A
Types of cables Type du conducteur Nominal cross section Sezione nominale Sektion nominale	0,2 ÷ 1,5 30 ÷ 16	mm² AWG
Stripping length Lunghezza spelatura Longueur de dénudage	6	mm
Torque Couple de serrage Coppia di torsione Drehmoment	0,3 / 2,5	Nm Lb-in
Temperature Température Temperatur	110	°C
Housing Corps isolant Corpo isolante Isolierkörper	PA - UL 94 V0	
Captive Screw Vis Imperdable Vite Imperdibile Unverlierbare Schraube	M2	
	0,5 x 2,5	
V	A	mm²/AWG
130	10	0,2 ÷ 1
130	10	0,2 ÷ 1
300	10	30 ÷ 16

min 2 - max 20		
VE	/ on demand GR GR1 NE AR BL RO GI	
D/A1		




CPA..SQ*

CPA

Single block · Blocco unico
Monobloc · Einzelblock



Poles · Poli · Pôles · Polzahl

2/10



7 - 7,62		
Pitch Pas	Passo Rastermaß	mm
Rated Voltage Tensione nominale Tension nominale	400 - 500	V
Rated Current Corrente nominale Bemessungsstrom	10	A
Types of cables Type du conducteur Nominal cross section Sezione nominale Sektion nominale	0,2 ÷ 1,5 30 ÷ 16	mm² AWG
Stripping length Lunghezza spelatura Longueur de dénudage	6	mm
Torque Couple de serrage Coppia di torsione Drehmoment	0,3 / 2,5	Nm Lb-in
Temperature Température Temperatur	110	°C
Housing Corps isolant Corpo isolante Isolierkörper	PA - UL 94 V0	
Captive Screw Vis Imperdable Vite Imperdibile Unverlierbare Schraube	M2	
	0,5 x 2,5	
V	A	mm²/AWG
450	10	0,2 ÷ 1
450	10	0,2 ÷ 1
300	10	30 ÷ 18

min 2 - max 10		
VE	/ on demand GR GR1 NE AR BL RO GI	
D/A1		



COB

Interlocking modules · Modulo componibile
Elements modulaires · Zusammensteckbare Blöcke



Poles · Poli · Pôles · Polzahl

2/3



5 - 5,08		
Pitch Pas	Passo Rastermaß	mm
Rated Voltage Tensione nominale Tension nominale	160	V
Rated Current Corrente nominale Bemessungsstrom	24	A
Types of cables Type du conducteur Nominal cross section Sezione nominale Sektion nominale	0,2 ÷ 4 30 ÷ 12	mm² AWG
Stripping length Lunghezza spelatura Longueur de dénudage	6	mm
Torque Couple de serrage Coppia di torsione Drehmoment	0,5 / 4	Nm Lb-in
Temperature Température Temperatur	110	°C
Housing Corps isolant Corpo isolante Isolierkörper	PA - UL 94 V0	
Captive Screw Vis Imperdable Vite Imperdibile Unverlierbare Schraube	M3	
	0,6 x 3,5	
V	A	mm²/AWG
130	24	0,5 ÷ 2,5
130	24	0,5 ÷ 2,5
300	16	24 ÷ 12

min 2 - max...		
GR	/ on demand VE	
D/A1		



* SQ Version = Horizontal version