


Recommended P.C.B Layout

MATERIAL

Contact Pin: Brass

Housing: PBT. UL94V-0

Plating: Gold Flash

SPECIFICATION

Current Rate: 3 AMP

Insulation Resistance: 5000MΩMin. at DC 500V

Contact Resistance: 20mΩMax. at DC 100mA

Dielectric Voltage: AC 500V for one minute

Operation Temperature: -40°C to + 105°C

POLES	DIM A	DIM B	DIM C
6	15.20	12.80	5.08
8	17.78	15.48	7.62
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
24	38.08	35.88	27.94
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.80	48.58	40.64
40	58.40	56.20	48.26
44	63.48	61.28	53.34
50	71.10	68.90	60.96
56	78.72	76.52	68.58
60	83.80	81.60	73.66
64	88.88	86.68	78.74

RoHS
Compliant

T&T

Connection System Co., Ltd.

APPD.
核准 BETTY

DWG.
製圖 BETTY

DATE 制表日
2009/02/26

SCALE
比例 參考

UNIT
單位 M M

PAGE
張數 1 OF 1

TOLERANCE
.0 =±.30
.00 =±.20
.000 =±.000
.0000=±.
ANG.=±3°

SIZE.
紙張尺寸 A 4

REV.
版次 A

PART NAME 品名

2.54 x 2.54 BOX HEADER
STRAIGHT RoHS

PART NO.

料號 BH-xx