

Dual Channel Power Driver

FEATURES

- Two independent Drivers
- 1.5A Totem Pole Outputs
- Inverting and Non-Inverting Inputs
- 40ns Rise and Fall into 1000pF
- High-Speed, Power MOSFET Compatible
- Low Cross-Conduction Current Spike
- Analog Shutdown with Optional Latch
- Low Quiescent Current
- 5V to 40V Operation
- Thermal Shutdown Protection
- 16-Pin Dual-In-Line Package
- 20-Pin PLCC and CLCC Package

DESCRIPTION

The UC1707 family of power drivers is made with a high-speed Schottky process to interface between low-level control functions and high-power switching devices - particularly power MOSFETs. These devices contain two independent channels, each of which can be activated by either a high or low input logic level signal. Each output can source or sink up to 1.5A as long as power dissipation limits are not exceeded.

Although each output can be activated independently with its own inputs, it can be forced low in common through the action either of a digital high signal at the Shutdown terminal or a differential low-level analog signal. The Shutdown command from either source can either be latching or not, depending on the status of the Latch Disable pin.

Supply voltage for both VIN and VC can independently range from 5V to 40V.

These devices are available in two-watt plastic "bat-wing" DIP for operation over a 0°C to 70°C temperature range and, with reduced power, in a hermetically sealed cerdip for -55°C to +125°C operation. Also available in surface mount DW, Q, L packages.


TRUTH TABLE (Each Channel)

INV.	N.I.	OUT
H	H	L
L	H	H
H	L	L
L	L	L

$\text{OUT} = \overline{\text{INV}} \text{ and N.I.}$

$\text{OUT} = \text{INV or N.I.}$

BLOCK DIAGRAM




ABSOLUTE MAXIMUM RATINGS

Supply Voltage, VIN, N/J-Pkg	40V
Collector Supply Voltage, VC, N/J-Pkg	40V
Output Current (Each Output, Source or Sink) Steady-State, N/J-Pkg	±500mA
Peak Transient	
N-Pkg	±1.5A
J-Pkg	±1.0A
Capacitive Discharge Energy	
N-Pkg	20mJ
J-Pkg	15mJ
Digital Inputs (See Note), N/J-Pkg	5.5V
Analog Stop Inputs, N/J-Pkg	VIN
Power Dissipation at TA = 25°C (See Note)	
N-Pkg	2W
J-Pkg	1W
Power Dissipation at T (Leads/Case) = 25°C (See Note)	
N-Pkg	5W
J-Pkg	2W
Operating Temperature Range	−55°C to +125°C
Storage Temperature Range	−65°C to +150°C
Lead Temperature (Soldering, 10 Seconds)	300°C

Note: All voltages are with respect to the four ground pins which must be connected together. All currents are positive into, negative out of the specified terminal. Digital Drive can exceed 5.5V if input current is limited to 10mA. Consult Packaging section of Databook for thermal limitations and considerations of package.


CONNECTION DIAGRAMS

DIL-16, SOIC-16 (TOP VIEW) J or N Package,



Note: All four ground pins must be connected to a common ground.

PLCC-20, LCC-20 (TOP VIEW) Q, L Packages




ELECTRICAL CHARACTERISTICS: Unless otherwise stated, these specifications apply for $T_A = -55^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ for the UC1707, -25°C to $+85^{\circ}\text{C}$ for the UC2707 and 0°C to $+70^{\circ}\text{C}$ for the UC3707; $V_{IN} = V_C = 20\text{V}$. $T_A = T_J$.

PARAMETERS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
V_{IN} Supply Current	$V_{IN} = 40\text{V}$		12	15	mA
V_C Supply Current	$V_C = 40\text{V}$, Outputs Low		5.2	7.5	mA
V_C Leakage Current	$V_{IN} = 0$, $V_C = 30\text{V}$, No Load		.05	0.1	mA
Digital Input Low Level				0.8	V
Digital Input High Level		2.2			V
Input Current	$V_I = 0$		-0.06	-1.0	mA
Input Leakage	$V_I = 5\text{V}$		.05	0.1	mA
Output High Sat., V_C - V_O	$I_O = -50\text{mA}$			2.0	V
	$I_O = -500\text{mA}$			2.5	V
Output Low Sat., V_O	$I_O = -50\text{mA}$			0.4	V
	$I_O = -500\text{mA}$			2.5	V
Analog Threshold	$V_{CM} = 0$ to 15V	100	130	160	mV
Input Bias Current	$V_{CM} = 0$		-10	-20	μA
Thermal Shutdown			155		$^{\circ}\text{C}$
Shutdown Threshold	Pin 7 Input	0.4	1.0	2.2	V
Latch Disable Threshold	Pin 3 Input	0.8	1.2	2.2	V

TYPICAL SWITCHING CHARACTERISTICS: $V_{IN} = V_C = 20\text{V}$, $T_A = 25^{\circ}\text{C}$. Delays measured to 10% output change.


PARAMETERS	TEST CONDITIONS	OUTPUT CL =			UNITS
From Inv. Input to Output		open	1.0	2.2	nF
Rise Time Delay		40	50	60	ns
10% to 90% Rise		25	40	50	ns
Fall Time Delay		30	40	50	ns
90% to 10% Fall		25	40	50	ns
From N.I. Input to Output					
Rise Time Delay		30	40	50	ns
10% to 90% Rise		25	40	50	ns
Fall Time Delay		45	55	65	ns
90% to 10% Fall		25	40	50	ns
V_C Cross-Conduction	Output Rise	25			ns
Current Spike Duration	Output Fall	0			ns
Analog Shutdown Delay	Stop non-Inv. = 0V	180			ns
	Stop Inv. = 0 to 0.5V	180			ns
Digital Shutdown Delay	2V Input on Pin 7	50			ns

SIMPLIFIED INTERNAL CIRCUITRY




The input common-mode voltage range is from ground to $(V_{IN}-3V)$. When not used both inputs should be grounded. Activate time is a function of overdrive with a typical value of 180ns. Pin 7 serves both as a comparator output and as a common digital shutdown input. A high signal here will accomplish the fastest turn off of both outputs. Note that "OFF" is defined as the outputs low. Pulling shutdown low defeats the latch operation regardless of its status.

Figure 1. Typical digital input gate.




The input zener may be used to clamp input signal voltages higher than 5V as long as the zener current is limited to 10mA max. External pull-up resistors are not required.

Figure 2. Typical digital input gate.



The Shutdown latch is disabled when pin 3 is open. An impedance of 4k or less from pin 3 to ground will allow a shutdown signal to set the latch which can then be reset by either recycling the V_{IN} supply or by momentarily ($>200ns$) raising pin 3 high.

Figure 3. Latch disable.



APPLICATIONS




Figure 6. Over-voltage protection.




Figure 7. Power MOSFET drive circuit.




Figure 8. Charge pump circuits.




Figure 9. Power bipolar drive circuit.

TRANSFORMER COUPLING




Figure 10. Transformer coupled MOSFET drive circuit.




Figure 11. Power MOSFET drive circuit using negative bias voltage and level shifting to ground reference PWM.

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
5962-87619012A	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	Level-NC-NC-NC
5962-8761901EA	ACTIVE	CDIP	J	16	1	TBD	A42 SNPB	Level-NC-NC-NC
5962-8761901V2A	ACTIVE	LCCC	FK	20	1	TBD	Call TI	Level-NC-NC-NC
5962-8761901VEA	ACTIVE	CDIP	J	16	1	TBD	Call TI	Level-NC-NC-NC
UC1707J	ACTIVE	CDIP	J	16	1	TBD	A42 SNPB	Level-NC-NC-NC
UC1707J/80313	OBSOLETE	CDIP	J	16		TBD	Call TI	Call TI
UC1707J/80900	ACTIVE	CDIP	J	16		TBD	Call TI	Call TI
UC1707J883B	ACTIVE	CDIP	J	16	1	TBD	A42 SNPB	Level-NC-NC-NC
UC1707JQMLV	ACTIVE	CDIP	J	16		TBD	Call TI	Call TI
UC1707L	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	Level-NC-NC-NC
UC1707L/81032	ACTIVE	LCCC	FK	20		TBD	Call TI	Call TI
UC1707L/81040	ACTIVE	LCCC	FK	20		TBD	Call TI	Call TI
UC1707L883B	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	Level-NC-NC-NC
UC2707DW	ACTIVE	SOIC	DW	16	40	TBD	CU NIPDAU	Level-2-220C-1 YEAR
UC2707DWTR	ACTIVE	SOIC	DW	16	2000	TBD	CU NIPDAU	Level-2-220C-1 YEAR
UC2707J	ACTIVE	CDIP	J	16	1	TBD	A42 SNPB	Level-NC-NC-NC
UC2707N	ACTIVE	PDIP	N	16	25	TBD	Call TI	Level-NA-NA-NA
UC2707Q	ACTIVE	PLCC	FN	20	46	TBD	Call TI	Level-2-220C-1 YEAR
UC2707QTR	ACTIVE	PLCC	FN	20	1000	TBD	Call TI	Level-2-220C-1 YEAR
UC3707DW	ACTIVE	SOIC	DW	16	40	TBD	CU NIPDAU	Level-2-220C-1 YEAR
UC3707DWTR	ACTIVE	SOIC	DW	16	2000	TBD	CU NIPDAU	Level-2-220C-1 YEAR
UC3707J	ACTIVE	CDIP	J	16	1	TBD	A42 SNPB	Level-NC-NC-NC
UC3707N	ACTIVE	PDIP	N	16	25	TBD	Call TI	Level-NA-NA-NA
UC3707Q	ACTIVE	PLCC	FN	20	46	TBD	Call TI	Level-2-220C-1 YEAR
UC3707QTR	ACTIVE	PLCC	FN	20	1000	TBD	Call TI	Level-2-220C-1 YEAR

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the

accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2005, Texas Instruments Incorporated